

GfA Checklist for <b>RSDs</b> (Roller Shutter Doors)		
Company:-		Contact Name:-
Job Ref:-		Contact No/email:-
Door Width (Cut lath size/Pin size)		Door Height (Centre Line)
Torre of Observer Mederical (Observer August 1997)		
Type of Shutter Material (Single Skin, Insulated, Weight/m2, Galvanised, Powder Coated or Perforated)		
Heavy Duty Bottom Rail		Type of Rail or Weight/m
	Yes No	
Windlocked Tube B		Tube Barrel Diameter & Wall Thickness
	Yes No	
Safedrive (Direct Drive) Options:-		
	Safedrive	Safedrive - Fi (High Speed)
Ranger/GT (Chain Drive) Options:-		
Ranger - Flangemount		GT/KE - Footmount
Inboard Mounting		Inboard Mounting
Outboard Mounting (replacements)		Outboard Mounting (replacements)
Sprung Barrel	Chain Drive :-	Gear Drive (replacements) :-
	Chain Pitch:	·
Yes No	No of Teeth - Sprocket: No of Teeth - Platewheel:	
NO	NO OF FEETH - Flatewheel.	Please provide a sketch if a more complicated Gear Train
Type of Control Panel		4 (Single Phase)
		1~ (Single Phase)
		3~ (3 Phase)
Safety Requirements Wired Safety Edge		
		Wireless Safety Edge
		Trifologo Carot, Lago

26.03.20



Identification:-

Please provide the rating plate data for existing GfA Drives Quote the 13 digit serial number shown on the left

Please send completed Checklist to GfA UK Ltd:
Scan & Email to - sales@gfa-elektromaten.co.uk or Fax to - 01926 336 417

GfA ELEKTROMATEN UK Ltd www.gfa-elektromaten.co.uk

Tel: +44 (0)1926 452 452 Fax: +44 (0)1926 336 417