

RX26-XPL5-GFA

The RX26-XPL5-GFA allows the easy operation and programming of the RX26-XPL whilst increasing the memory to 500 transmitters and adding an IP55 enclosure.

The XPL5 comes 2 relays allowing use of 2 button transmitters from GFA. Each relay can be separately configured for pulse, timed or latch modes, with a maximum contact rating of 24VA at 60V. Security is upheld by the use of Keeloq rolling code decryption.



RX26-XPL5

Overview

- 12-24V AC/DC Supply
- 24VA Contact Rating (max 60V)
- 2 Relays (1 x NO-Com-NC & 1 Com-NO)
- Selectable Latch (step), Pulse or Timed Output
- Backlit LCD Display For Easy Programming
- 500 Transmitter Memory
- Single Transmitter or Full Memory Erasure
- Memorization PLUS
- Rolling Code (Keeloq) @ 433Mhz
- Input for SEA433 External Antenna
- IP55 Enclosure
- Can only be used with GFA transmitters



RX26-XPL
with lid

RX26-XPL5-GFA - Technical Specifications

Product Specifications

Receiver type: Supereheterodyne
Memory capacity: 500 transmitters
Demodulation: AM/ASK
Frequency: 433.92 Mhz
Sensitivity (for good signal): -115 dBm
Encoding: Keeloq hopping code
Number of code combinations: 2exp64
IP Rating: IP55

Electrical Specifications

Input load: 50 Ohm
Power supply: 12 to 24Vac/dc
Current consumption (@12Vdc): 25mA to 90mA (max)

Relays

Number of relays: 2
Relay contacts: 1 NO and 1 NO/NC
Max current on relay output: 24VA max 60V
Relay operating mode: pulse, step, timed
Delay: from 1sec. to 23h59min

Dimensions

Dimensions: 123 x 81,5 x 41,5mm
Weight: 65gr
Environment: -20°C to 70°C