

# GfA-Stick with GfA+ App

## Description

The memory of the door controls TS 959, TS 970 or TS 971 can be read out and displayed via Bluetooth® 4.0 using the GfA-Stick and the GfA+ App.

All settings are saved in the GfA cloud per 3G/4G or WiFi. The saved data is accessible at any time through the GfA-Portal.

The GfA-Stick plugs into the TS door controls limit switch port and the door control is set to communication mode ready for data transfer.

## GfA-Stick



Designation	Part no.
GfA-Stick	20003696

## App function "TS-data collector"

This function establishes a Bluetooth® connection between the smartphone and the GfA-Stick. After successful connection, the intended TS door control appears on the display of the smartphone. Optionally the data record can be marked with an indication of the location, a reference number or free text.

## App function "Read TS-data"

This function starts the transfer of the data between door control and the smartphone. The data is displayed on five clear pages:

### ■ General

Displays information i.e. serial number, software version and current temperature

### ■ Current programming

This page shows the current settings of the TS door control programming parameters

### ■ Last faults

The faults page displays the last six faults

### ■ Events

A record of the last 128 events is shown

### ■ Saved programming

Saved program settings can be displayed even after the door control has been reset to factory defaults

## App function "Last TS-data"

The last ten read out records are displayed.

## Registration on the GfA-Portal

■ <https://portal.gfa-elektromaten.de/en>

## Appropriate GfA door controls (housing TS-B)

- TS 959
- TS 970
- TS 971

## Operating systems with Bluetooth® 4.0 support

- Android 4.3 or higher
- iOS 5 or higher

## Smartphones (examples)

- Samsung Galaxy S3 - S5
- iPhone 5 /6